

Foratura a secco

**T1800 162 MS
T1800 162 MS-EL
T1800 162 MA-EL**



**T1800 162 PS-EL
T1800 162 PA-EL**



Impugnatura a pistola.
Pistol grip.

Foratura a secco e ad acqua

**T1800 20 MU-EL
T1800 102 MU-EL
TALPA 1 MU-EL**



**T1800 20 PU-EL
T1800 102 PU-EL
TALPA 1 PU-EL**



Impugnatura a pistola.
Pistol grip.

Foratura a secco e ad acqua

**T1800 102 ME-EL
TALPA 1 ME-EL**



**T1800 102 PE-EL
TALPA 1 PE-EL**



Impugnatura a pistola.
Pistol grip.

<carotatrici manuali> <light hand held core drills>

	T1800 162 MS	T1800 162 MS-EL	T1800 162 PS-EL	T1800 162 MA-EL	T1800 162 PA-EL	T1800 102 MU-EL	T1800 102 PU-EL	T1800 102 ME-EL	T1800 102 PE-EL	T1800 20 MU-EL	T1800 20 PU-EL	TALPA 1 MU-EL	TALPA 1 PU-EL	TALPA 1 ME-EL	TALPA 1 PE-EL	
Tensione V Voltage	230 / 50 - 60 HZ															
Potenza W Power	1800	1800	1800	1800	1800	1800	1800	1800	1800	1800	1800	2200	2200	2200	2200	
N° velocità N. speed	1	1	1	1	1	1	1	1	1	1	1	3	3	3	3	
Velocità a vuoto rpm Idle speed	1300	1300	1300	1300	1300	830	830	830	830	5130	5130	750 1800 2500	750 1800 2500	750 1800 2500	750 1800 2500	
Capacità in muratura mm Capacity in masonry	30 ÷ 162	30 ÷ 162	30 ÷ 162	30 ÷ 162	30 ÷ 162	50 ÷ 122	50 ÷ 122	50 ÷ 122	50 ÷ 122	10 ÷ 50	10 ÷ 50	20 ÷ 160	20 ÷ 160	20 ÷ 160	20 ÷ 160	
Capacità in calcestruzzo mm Capacity in concrete	30 ÷ 140	30 ÷ 140	30 ÷ 140	30 ÷ 140	30 ÷ 140	50 ÷ 102	50 ÷ 102	50 ÷ 102	50 ÷ 102	10 ÷ 20	10 ÷ 20	20 ÷ 150	20 ÷ 150	20 ÷ 150	20 ÷ 150	
Attacco corona Bit connection	M18 5/8" M16	M18 5/8" M16	M18 5/8" M16	1"1/4	1"1/4	1"1/4 1/2" GAS	1"1/4	1"1/4	1"1/4			1"1/4 1/2" GAS	1"1/4	1"1/4	1"1/4	
Frizione meccanica Mechanical clutch	dischi in bronzo brass rings															
Elettronica multifunzione Multi function electronic	-	-	-	-	-	soft start, frizione elettronica soft start, electronic clutch										
Interruttore differenziale PRCD	no	no	no	no	no	si	si	si	si	si	si	si	si	si	si	si
Peso kg Weight	4,6	4,6	4,6	4,6	4,6	5	5	5	5	5	5	7,3	7,3	7,3	7,3	
Attacco aspiratore Dust extraction	no	no	no	si	si	no	no	si	si	no	no	no	no	no	si	si
Perforazione a secco/dry ad acqua/wet																

CORONE DIAMANTATE DIAMOND CORE DRILL BITS

CORONE - Attacco 1"1/4 - GAMMA STANDARD Ø da 41 a 501 mm
CORE DRILL BITS - 1"1/4 coupling - STANDARD RANGE Ø from 41 to 501 mm

CORONE - Attacco 1"1/4 - GAMMA PREMIUM Ø da 41 a 501 mm
CORE DRILL BITS - 1"1/4 coupling - PREMIUM RANGE Ø from 41 to 501 mm

CORONE - Attacco M16 - USO MANUALE Ø da 22 a 202 mm
CORE DRILL BITS - M16 coupling - MANUAL USE Ø from 22 to 202 mm

FORETTI - Attacco 1/2" gas - TAGLIO A SECCO E AD ACQUA Ø da 10 a 201 mm
SMALL DRILLS - 1/2" gas coupling - WET AND DRY CUT Ø from 10 to 201 mm

